

Automatic parts cleaners have many applications, including production, maintenance, servicing and metal processing. Parts cleaners work without solvents and use water-based solutions.

Standard accessories:

- Operating hour meter
- Containment ring (stainless for rotary table)
- Caster wheels
- 2 lockable
- Timer for cleaning cycle
- Water level monitoring

Order number: 1.626-703.0

**Technical data**

Pressure (bar/MPa)	1.5/0.15
Water flow rate (l/h)	4500
Connected load	5.5
Working diameter (mm)	600
Working Area (mm)	-
Usable height (mm)	310
Housing / frame	Stainless Steel (1.4301)
Tested by	CE
Heating output	4.5
Max. temperature (°C)	80
Adjustable cleaning time (min.)	1-30
Load capacity (kg)	130
Sound pressure level (dB(A))	65
Tank capacity (l)	100
Number of current phases (Ph)	3
Frequency Hz	50
Voltage V	400
Weight (kg)	195

Parts cleaning

PC 60/130 T



Technical data

Dimensions (D x W x H) (mm)

1080x1000x1250

Details

Description

With a fully automatic cleaning cycle, the PC 60/130 T saves time and money, whilst guaranteeing superb results every time. The parts are simply placed on an electrically driven turn table, which then rotates at a constant speed. The intensive cleaning action is achieved using water based cleaning agents which remove grease, oils and other contamination effortlessly. Excess oil is then removed automatically from the solution via the integrated oil separator, giving the cleaning agent a longer cleaning life. The cleaning agent consists of 95 - 99% water and 1 - 5% alkaline agent.

Application

- Parts cleaning
 - Degreasing
 - Oil removal
-

Features & Benefits

- Fully automatic cleaning cycle runs unattended, leaving operators free to carry out other duties
 - Oil separator extends the life of the cleaning solution (optional)
 - Short wash cycles available (5 - 10 minutes)
 - Water based cleaning solution contains no solvents
 - Simple and easy to understand operations
 - Level sensor prevents the unit from running when the solution is too low
 - Integrated overload protection of the washing cart drive
 - Stainless steel construction
-

Accessories

Parts cleaner

2-channel timer

2-channel timer module to control the heating and oil skimmer of the parts cleaners fully automatically. The heating and oil skimmer can be programmed independently for every weekday.

Order number 6.631-551.0



Add-on kit Skimmer

Order number 2.642-465.0



Add-on kit filter PC

Order number 2.642-193.0



Container small

Order number 6.626-086.0



Order number 6.626-081.0

