

Manually-steered operated floor scrubber with roller brushes with a performance up to 1840 m²/h.For economic basic cleaning, maintenance cleaning.

Standard accessories:

- Disc brush
- Tank-in-tank system
- · Mains operation

Order number: 1.127-342.0



Technical data

| Working width, brush (mm) | 460 |
|--------------------------------|---------------|
| Working width, vacuum (mm) | 850 |
| Motor rating (W) | 1700 |
| Battery Capacity | - |
| Battery Voltage | - |
| Tank fresh/dirt water (I) | 55/55 |
| Brush contact pressure (g/cm²) | 27 |
| Brush rotation speed rpm | 200 |
| Max. area performance (m²/h) | 1840 |
| Frequency Hz | 50 |
| Voltage (V) | 220-230 |
| Weight (kg) | 55 |
| Dimensions (L x W x H) (mm) | 1250x560x1070 |
| | |



Deta8ls

Description

Compact size but full performance. The BD 530 Ep offers a great price performance ratio. The ease of use and maintenance is reflected in the classical design. The machine is easy to maintenance, all components are easy to access.

Features & amp; Benefits

Electric powered:

- Work is not time limited. Several cleanings per day are possible.

Through light weight also adaptable for elastic surfaces.

55 I tank

- 40 % higher tank capacity by using the battery compartment as tank
- 40 % increased area performance until refilling
- Unchanged compact dimensions
- Wheels are mounted direct at the tank (without steel frame)

Simple transport wheel

- Good fixing at the brush head
- Easy to use
- Easy foldable for cleaning
- Simple construction



Accessories

Disc Brushes for BD

Disc brush, medium

red, for all surfaces

Order number 6.906-054.0



Disc brush, hard

black, for deep cleaning

Order number 6.906-055.0



Disc brush, soft

natural, for polishing

Order number 6.906-056.0



Disc brush, very soft

white, for maintenance cleaning or polishing

Order number 6.906-552.0



Microfibre pad

Pad microfibre

Excellent cleaning power. Cleans even pores of fine stonware tiles.

Order number 6.369-960.0





Miscellaneous

Filling hose

Filling hose, 1500 mm. With universal funnel. Facilitates machine filling from a water tap.

Order number 6.389-524.0



Extension cable

Extension cable, 20 m, 3x1.5 mm². With splash-proof earthing pin plug, strain relief and anti-kink sleeve.

Order number 6.647-022.0



Cleaning agent dosage kit, wall mounted DS 3

Directly connectable with the tab, water and detergent will be filled in the fresh water tank in the preset mixture. Can also be used with filling system kit.

Order number 2.641-811.0



Pad drive board

Pad drive board

Order number 6.906-332.0



Pads

Pad, hard, 457 mm

5 pads, hard, black, 457 mm diameter. For removing stubborn dirt and basic cleaning. Suitable for, e.g. D 90.

Order number 6.369-022.0





Pads

Pad, medium-hard, 457 mm

5 pads, medium-hard, green, 457 mm diameter. For removing stubborn dirt and basic cleaning. Suitable for, e.g. D 90.

Order number 6.369-023.0



Pad, mean value soft, 457 mm

5 pads, medium-soft, red, 457 mm diameter. For cleaning all floors. Suitable for, e.g. D 90.

Order number 6.369-024.0



Squeegees for suction bars

Squeegee blade, oil-resistant, grooved, 890 mm

Squeegee blade kit includes front and rear squeegee blades, 870 mm. Grooved squeegee blades of hard-wearing, oil-resistant, transparent polyurethane. For all standard floors.

Order number 6.273-207.0



Squeegee blade, oil-resistant, slotted, 890 mm.

Squeegee blade kit includes front and rear squeegee blades, 870 mm. Slotted squeegee blades of hard-wearing, oil-resistant, transparent polyurethane. For sensitive floors.

Order number 6.273-229.0



Sucking lip of natural rubber, 890 mm

Squeegee blade kit includes front and rear squeegee blades, 870 mm. Soft natural rubber grooved squeegee blades. For all standard floors.

Order number 6.273-213.0





Suction bar, complete

Squeegee, straight

Straight, without supporting rolls. Squeegees consist of soft natural rubber.

Order number 4.777-306.0



Squeegee, curved

Curved, without supporting rolls. Squeegees consist of soft natural rubber.

Order number 4.777-316.0

